

C350

SPECIFICATION SHEET



DESCRIPTION

- 4-IN-1 LED multi-application dimmable electronic control gear manufactured by a DALI member of DiiA.
- DALI-2, Push-Dim, 0-10V and 10V PWM functions
- 650-1100mA (Selectable every 50mA, Pre-selected 650mA)
- 46.2W Max Power Output
- Output voltage ranging between 14V and 42V
- 200-240VAC 47~63Hz input
- Tested in DALI House according to IEC 62386 part 102 (DALI-2) 207
- Reliable, Class 2, SELV to EN61347
- Independent and complete with Strain Relief
- Permissible AC cable 0.5-1.5mm² wire gauge, 3.5~8mm PVC cover diameter
- Built-in active PFC
- Flicker Free
- DALI-2 tested & qualified
- Manufactured by a DALI member, compatible with universal DALI controllers
- 5 Year Guarantee

CLASSIFICATION



DIMENSIONS/DRAWING

Length: 125mm
Width: 76mm
Height: 30mm

FINISH

Emco House, Units 6-10, Marshgate Drive
Hertford, Hertfordshire, SG13 7JY, UK

Subject to change without prior notice. E & OE.

sales5@emcogroup.co.uk Tel: 01992 582033
www.emcogroup.co.uk Fax: 01992 582044