

CDFRLED

SPECIFICATION SHEET



UNIQUE DESIGN

230V Driver easily detached from electrical connections by clip

2 x 1.5 Easifix connections

Terminal cover



DESCRIPTION

- 8.5W dimmable 30/60/90 minute IP65 Fire rated downlight.
- Internal baffle for anti-glare
- 3000K
- 600lm, 71lm/W
- 20° tilt adjustable gimbal.
- Simply connect 2 x 1.5mm cables into the connector that plugs straight into the driver. This enables circuit testing to be carried out with little effort
- Part B - Fire Rated 30/60/90 Minute Compliant Tested
- Part C - Moisture Compliant
- Part E - Acoustic Compliant
- Part L1 Compliant
- 5 Year Guarantee

CLASSIFICATION

CE IP65 RoHS



DIMENSIONS/DRAWING

Cutout: \varnothing 76mm
Diameter: \varnothing 90mm
Total Depth: 75mm

FINISH

MATT WHITE

SATIN SILVER

CODE	WATTAGE	COLOUR TEMP.	BEAM ANGLE	LUMENS	LUMENS/W
CD FRLED838	8.5W	3000K	38°	600lm	71lm/W
CD FRLED860	8.5W	3000K	60°	600lm	71lm/W

Emco House, Units 6-10, Marshgate Drive
Hertford, Hertfordshire, SG13 7JY, UK

Subject to change without prior notice. E & OE.

sales5@emcogroup.co.uk
www.emcogroup.co.uk

Tel: 01992 582033
Fax: 01992 582044