

# EMLEDBMST

SPECIFICATION SHEET

## AUTO-TEST & REMOTE CONTROL



- \* Press 1 time to create the function test;
- Press 2 times to create the full duration test, and press again to stop the test.
- Long press for 12s to renew the self-test program.
- Requires Remote Control\*

### DESCRIPTION


- 3W IP65 Slim style Maintained / Non-maintained bulkhead.
- 6000K-6500K
- Hinged screwless gear tray for ease of installation
- 210lm (160lm emergency)
- Input voltage 220-240v
- Running Current: 350mA
- 5 x 20mm knockouts / rear besa box entry
- 3.2V 1500mAh Hi-temperature LiFePO4 battery
- Clear polycarbonate diffuser & ABS polyester base
- Includes multi directional legend sticker kit
- Operating temp.: 0°C to 40°C
- 3hr maintained (can be wired as non-maintained)
- 5 Year Guarantee ( 3 Year Battery Guarantee)

### CLASSIFICATION

CE IP65 RoHS



### DIMENSIONS/DRAWING



### FINISH

WHITE

Emco House, Units 6-10, Marshgate Drive  
Hertford, Hertfordshire, SG13 7JY, UK

*Subject to change without prior notice. E & OE.*

sales@emcogroup.co.uk Tel: 01992 582033  
www.emcogroup.co.uk Fax: 01992 582044

**emcogroup**  
LIMITED

emcolite

emcosafe

emcovent

**EMCOLED**

**FIREBLOK**

**rio**