

LBHCD65

SPECIFICATION SHEET



DESCRIPTION


- 15W IP65 IK08 4000K LED BULKHEAD
- 1000lm
- 2 x 20MM Conduit Entry
- Optional Emergency & Microwave Functions (Emergency Output: 200lm)
- IK08: Vandal Resistant
- 120° Beam Angle
- PF: >0.9, CRI: 82
- AC 90-265V, 50-60Hz
- 24 Pc's 5730 LED
- UV stabilized PC housing with ABS Base
- Surface Mounted
- 50,000 Hour Lifetime
- 2 Years Warranty

CODE	OPTIONS
LBHCD65	Standard
LBHCD65MS	Microwave sensor
LBHCD65M3	3 hours emergency backup
LBHCD65MSM3	Microwave sensor and 3 hours emergency backup

CLASSIFICATION



DIMENSIONS/DRAWING



FINISH



Emco House, Units 6-10, Marshgate Drive
Hertford, Hertfordshire, SG13 7JY, UK

Subject to change without prior notice. E & OE.

sales5@emcogroup.co.uk Tel: 01992 582033
www.emcogroup.co.uk Fax: 01992 582044

emcogroup
LIMITED

emcolite

emcosafe

emcovent

EMCOLED

FIREBLOK

rio